

Customer Enquiry
 Order _____

To

Company	LiftEquip GmbH Elevator Components
Contact person	
Phone	+49 (7158) 12-2929
Fax	+49 (7158) 12-2971
E-Mail	Kontakt@liftequip.de
Date	

Material of rope pulley	<input type="checkbox"/> Cast steel	<input type="checkbox"/> Polyamide*
Rope pulley diameter [mm]	<input type="checkbox"/> 150 <input type="checkbox"/> 260	<input type="checkbox"/> 360 <input type="checkbox"/> 400
	<input type="checkbox"/> 450 <input type="checkbox"/> 540	<input type="checkbox"/> 640 <input type="checkbox"/> 740
Rope diameter [mm]	<input type="checkbox"/> 6 <input type="checkbox"/> 6,5 <input type="checkbox"/> 8	<input type="checkbox"/> 10 <input type="checkbox"/> 12
	<input type="checkbox"/> 13 <input type="checkbox"/> 16 <input type="checkbox"/> 18	<input type="checkbox"/> _____

Number of grooves of rope pulley _____

Groove distance RA [mm] _____

Bearing type of rope pulley Standard High load

Axle for Rope pulley Yes No

Axle bracket Yes No

Rope pulley load [kN] _____

Rope speed [m/s] _____

Notes:

Rope pulleys for double wrapping – DW (double wrap) see technical folder, standard sheet 60 720 12 00 0, sheet 2

* Polyamide rollers only in the versions:

260 mm, 6x6.5, RA11

360 mm, 7x8, RA14

450 mm, 7x10, RA 18/20